Kingfisher Lighting

Datasheet



Story

Product Description

A traditional lantern shape with a modern twist.

Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 99.0 lm/W and will be capable of producing up to 6,650 luminaire lumens at 4000K with a CRI >70. It shall have symmetric optics and is rated at IP66 and IK08.

Specification

Weight: 9kg max
Windage: 0.07-0.15m²
Material: Die-cast Aluminium
Paint finish: Graphite Grey

Key Features

- 17.0W - 79.0W
- 1,690 - 6,650 Luminaire Lumens
- Efficacy up to 99.0 lm/W
- 4000K, CRI >70
- Lifetime >100,000hr, L90

AEC ILLUMINAZIONE

light life

LED | IP66 | IK08 | DIM | Control Compatible

Mounting Options


- Post Top 76mm

Other Options

- Colour Temperature Options
- Paint Finish Options

Contact for details

Optics



Symmetrical optic for urban areas

Code	Power	Luminaire Lumens	No. Modules	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included	Driver Type
STORTP-SO5-4.15-4M1F	17.0	1,690	4	150		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-SO5-4.25-4M1F	28.5	2,750	4	250		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-SO5-4.35-4M1F	39.5	3,730	4	350		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-SO5-4.42-4M1F	47.5	4,380	4	420		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-SO5-4.5-4M1F	59.0	5,290	4	525		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-SO5-4.7-4M1F	79.0	6,650	4	700		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-S-4.15-4M1F	17.0	1,690	4	150	Asymmetrical Street Optic (S)	4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-S-4.25-4M1F	28.5	2,750	4	250		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-S-4.35-4M1F	39.5	3,730	4	350		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-S-4.42-4M1F	47.5	4,380	4	420		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-S-4.5-4M1F	59.0	5,290	4	525		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-S-4.7-4M1F	79.0	6,650	4	700		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-HCS-4.25-2M1F	25.5	2,420	2	250		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-HCS-4.35-2M1F	35.0	3,170	2	350		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-HCST-4.25-1M1F	13.5	1,210	1	250		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-HCST-4.25-2M1F	25.5	2,420	2	250	Asymmetrical Hyper Comfort (HC-ST)	4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-HCST-4.35-1M1F	18.5	1,580	1	350		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI
STORTP-HCST-4.35-2M1F	35.0	3,170	2	350		4000	IP66	IK08	9.0	Graphite Grey	Driver Inc	DALI



Dimensions

