




The elegance of the circle.
MIKO [Range]



Façade



Bollard



Urban

The coordinated Range for every lighting project

MIKO Range comprises three types of products that allow to design aesthetically coordinated projects with high visual comfort. High resistant and performing materials are used to assure durability and quality of the series.



Applications



Façade

Both for indoor and outdoor lighting, MIKO Façade has an high protection degree (IP66).



Bollard

Elegant design to add a stylish touch to residential and urban environments.



Urban

MIKO Grande is the future-proof post-top luminaire which does not produce lighting pollution.



MIKO Grande
available with **Zhaga**
Book 18 and **Nema**
ANSI C136.41
connection
interfaces.

MIKO Façade

MIKO wall mounted

Simple and impactful at the same time.

Available in different colors to better satisfy projects requirements, this wall-mounted, die-cast aluminium luminaire emanates a soft light that enhances volumes and materials of indoor and outdoor spaces.



Façade
versions available


STANDARD PRODUCT		OPTIONS AVAILABLE	
Wiring	ON/OFF (A)	CCT	4000K
CCT	3000K (-830)	Colors	● 16 (-16) Grey, similar to (RAL 7024), ○ 11 (-11) White, ● 12 (-12) Black, ● 23 (-23) Corten
Colors	● 21 (-21) Aluminium (RAL 9006)		




MIKO | Façade



dimensions
(mm)



Code	Optic	Watt	Lumen	CRI	CCT	Class	Wiring	Power Supply	A	B	C
0470000A-830-21	 radial	10W	875lm	80	3000K	⊕	ON/OFF	220-240V 50/60Hz	200	100	76



MIKO Bollard

A touch of elegance

For every lighting project.

Available in different heights, color temperatures, with no-glare one way or radial optic, this bollard harmoniously illuminates private or public gardens, pathways, pedestrian areas and parks.



Bollard

versions available

STANDARD PRODUCT

Wiring	ON/OFF (A)
CCT	3000K (-830)
Colors	● 21 (-21) Aluminium (RAL 9006)

AVAILABLE OPTIONS


Wiring	DALI (B)
CCT	4000K (-840)
Colors	● 16 (-16) Grey, similar to (RAL 7024), ● 12 (-12) Black, ● 23 (-23) Corten



MIKO | one way



dimensions
(mm)





Code	Optic	Watt	Lumen	CRI	CCT	Class	Wiring	Power Supply	A	B	C
0872004A-830-21	one way	10W	800lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	300
0872005A-830-21	one way	10W	800lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	600
0872006A-830-21	one way	10W	800lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	800
0872007A-830-21	one way	10W	800lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	1000

MIKO | radial

Code	Optic	Watt	Lumen	CRI	CCT	Class	Wiring	Power Supply	A	B	C
0872000A-830-21	radial	20W	1700lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	300
0872001A-830-21	radial	20W	1700lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	600
0872002A-830-21	radial	20W	1700lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	800
0872003A-830-21	radial	20W	1700lm	80	3000K	□	ON/OFF	220-240V 50/60Hz	200	76	1000









TECHNICAL INFORMATION



MIKO Bollard
available in 4
heights: 300, 600,
800 e 1000mm.




ACCESSORIES	Descriptions	Weight
1099396X-21	Base plate with galvanized steel tie rods. Height 140mm.	0,40Kg
1099334X	Galvanized steel base plate for ground anchoring.	1,70Kg
1099339X	Galvanized steel stake (only for bollard with height 300mm).	0,25Kg
1099335X	Galvanized steel base plate for ground anchoring with internal galvanized steel pole reinforcement structure. H 124mm (C=300).	1,50Kg
1099336X	Galvanized steel base plate for ground anchoring with internal galvanized steel pole reinforcement structure. H 424mm (C=600).	2,30Kg
1099337X	Galvanized steel base plate for ground anchoring with internal galvanized steel pole reinforcement structure. H 624mm (C=800).	2,90Kg
1099338X	Galvanized steel base plate for ground anchoring with internal galvanized steel pole reinforcement structure. H 824mm (C=1000).	3,50Kg
1099259X	Junction box IP68 - 4 entries - 2/3 poles.	0,05Kg



MIKO Grande

Future-proof lighting.

Lighting is playing a central role in building and shaping smart cities. MIKO Grande is equipped with connection interfaces and it can be installed on wall by means of pole heads, or on single/double pole attachments.



Urban lighting

available versions

STANDARD PRODUCT


Wiring	ON/OFF (A)
CCT	4000K (-840)
Colors	● 21 (-21) Aluminium (RAL 9006)

AVAILABLE OPTIONS

Wiring	DALI (B), BIP (E)
CCT	3000K (-830)
Colors	● 16 (-16) Grey, similar to (RAL 7024), ● 12 (-12) Black




MIKO Grande | comfort



Code	Optic	Watt	Lumen	CRI	CCT	Class	Wiring	Power Supply	A	B	C
0886012A-840-21	 type II	30W	3100lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886013A-840-21	 type II	48W	4800lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886014A-840-21	 type III	30W	3300lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886015A-840-21	 type III	48W	5100lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886016A-840-21	 type IV	30W	3400lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886017A-840-21	 type IV	48W	5200lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886018A-840-21	 type IV-L	30W	3300lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886019A-840-21	 type IV-L	48W	5100lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886010A-840-21	 type VS	30W	3200lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886011A-840-21	 type VS	48W	5400lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-





MIKO Grande | performance



Code	Optic	Watt	Lumen	CRI	CCT	Class	Wiring	Power Supply	A	B	C
0886002A-840-21	 type II	30W	3400lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886003A-840-21	 type II	48W	5300lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886004A-840-21	 type III	30W	3600lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886005A-840-21	 type III	48W	5600lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886006A-840-21	 type IV	30W	3700lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886007A-840-21	 type IV	48W	5700lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886008A-840-21	 type IV-L	30W	3600lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886009A-840-21	 type IV-L	48W	5600lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886000A-840-21	 type VS	30W	3500lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-
0886001A-840-21	 type VS	48W	5900lm	80	4000K		ON/OFF	220-240V 50/60Hz	360	305	-

See technical information about "performance" versions in the following pages.




Urban lighting



available pole installations

- suitable for pole with **Ø 60mm** reduction (H=100mm) - See accessory Code: **1099566X-21**

- suitable for pole with **Ø 76mm** reduction (H=100mm) - See accessory Code: **1099567X-21**



TECHNICAL INFORMATION (performance)





type II

H=5m

LUX (m)

Code:
0886003A




type III

H=5m

LUX (m)

Code:
0886005A




type IV

H=5m

LUX (m)

Code:
0886007A




type IV-L

H=5m

LUX (m)

Code:
0886009A





type VS

H=5m

LUX (m)

Code:
0886001A

ACCESSORIES	Description	Peso
1099098X-21	Coated die-cast aluminium wall bracket for arm Ø 60 mm.	2,50Kg
1099097X-21	Coated die-cast aluminium single pole attachment.	3,50Kg
1099096X-21	Coated die-cast aluminium double pole attachment.	6,00Kg
1099566X-21	Locking ring and counter-ring for pole Ø60mm	0,03Kg
1099567X-21	Locking ring and counter-ring for pole Ø76mm	0,05Kg





Find **MIKO [Range]**
in the new Catalogue

ARCHITECTURAL LIGHTING EXTERIOR 2023

Completely dedicated to outdoor lighting solutions.
A practical and complete tool for lighting professionals.

Download the digital version from the website arcluce.it
or request the hard copy to info@arcluce.it



Arcluce S.p.A.

Via 1° Maggio, 6
20070 - San Zenone al Lambro (Milan) Italy

Phone +39 02 9810981
E-mail info@arcluce.it
Website arcluce.it