

Datasheet

Revelampe

Product Description

Revelampe is a classic design encompassing modern LED technology. The AEC Comfort Light Optic™ is an integral part of the design, making it ideal for public areas.

Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 129.0 lm/W and will be capable of producing up to 12,300 luminaire lumens at 4000K with a CRI >70. It shall have asymmetric optics and is rated at IP66 and IK08.

Specification

Weight: 8.0-11.5kg
 Windage: Revelampe LL32 0.7-0.15m²
 Revelampe LL35 0.09-0.25m²
 Material: Die-cast Aluminium
 Paint finish: Graphite Grey

Key Features

- 16.0W - 102.0W
- 1,840 - 12,300 Luminaire Lumens
- Efficacy up to 129.0 lm/W
- 4000K, CRI >70
- Lifetime >100,000hr, L90







Mounting Options

- Suspended Mount 1/2" Gas Connection

Other Options

- Colour Temperature Options
 - Paint Finish Options
- [Contact for details](#)

Optics

<p>S05</p> 		<p>Asymmetrical optic suitable for street, urban and green areas</p>
<p>STE-M</p> 		<p>Asymmetrical optic suitable for suburban areas</p>

Code	Power	Luminaire Lumens	No. Modules	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included	Driver Type
REVELL32-SO5-4.5-1M1F	16.0	1,840	1	525	Asymmetrical Street Optic (SO5)	4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL32-SO5-4.7-1M1F	21.5	2,370	1	700		4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL32-SO5-4.5-2M1F	30.5	3,620	2	525		4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL32-SO5-4.7-2M1F	40.0	4,630	2	700		4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.5-1M1F	16.0	1,840	1	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.7-1M1F	21.5	2,370	1	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.5-2M1F	30.5	3,620	2	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.7-2M1F	40.0	4,630	2	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.5-3M1F	44.0	5,420	3	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.7-3M1F	58.0	6,890	3	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.5-4M1F	57.0	7,010	4	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-SO5-4.7-4M1F	76.0	8,810	4	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.5-1M1F	16.0	1,840	1	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.7-1M1F	21.5	2,330	1	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.5-2M1F	30.5	3,620	2	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.7-2M1F	40.0	4,630	2	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.5-3M1F	44.0	5,420	3	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.7-3M1F	58.0	6,890	3	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.5-4M1F	57.0	7,010	4	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-SO5-4.7-4M1F	76.0	8,810	4	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI

Code	Power	Luminaire Lumens	No. Modules	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included	Driver Type
REVELL32-STE-M-4.5-1M1F	21.5	2,560	1	525	Asymmetrical Street Optic (STE-M)	4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL32-STE-M-4.7-1M1F	28.0	3,200	1	700		4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL32-STE-M-4.5-2M1F	39.0	5,060	2	525		4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL32-STE-M-4.7-2M1F	52.0	6,400	2	700		4000	IP66	IK08	8.0	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.5-1M1F	21.5	2,560	1	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.7-1M1F	28.0	3,200	1	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.5-2M1F	39.0	5,060	2	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.7-2M1F	52.0	6,400	2	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.5-3M1F	57.0	7,340	3	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.7-3M1F	76.0	9,230	3	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.5-4M1F	76.0	8,810	4	525		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELL35-STE-M-4.7-4M1F	102.0	12,300	4	700		4000	IP66	IK08	11.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.5-1M1F	21.5	2,560	1	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.7-1M1F	28.0	3,200	1	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.5-2M1F	39.0	5,060	2	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.7-2M1F	52.0	6,400	2	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.5-3M1F	57.0	7,340	3	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.7-3M1F	76.0	9,230	3	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.5-4M1F	76.0	8,810	4	525		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI
REVELR55-STE-M-4.7-4M1F	102.0	12,300	4	700		4000	IP66	IK08	10.5	Graphite Grey	Driver Inc	DALI



Dimensions

All units of measurement in mm

