

# Datasheet

## Tauri



### Product Description

With its symmetrical distribution and modern looks, Tauri is made for the urban and out of town landscape. With two optics and a range of lamp and gear types, including LED, Tauri is flexible and practical.

### Specification Text

The luminaire shall be manufactured from high-pressure Polycarbonate. It shall have an LED efficacy of up to 71.0 lm/W and will be capable of producing up to 3,905 luminaire lumens at 4000K with a CRI >70. It shall have a symmetric optic and is rated at IP66 and IK09.

### Specification

Weight: 5.9 - 6.0kg  
Windage: 0.15m<sup>2</sup>  
Material: Polycarbonate  
Paint finish: RAL7016 Anthracite Grey Finish

### Key Features

- 35.0 - 55.0W
- 2,487 - 3,905 Luminaire Lumens
- Efficacy up to 71.0 lm/W
- 4000K, CRI >70
- Lifetime >100,000hr, L90




### Mounting Options

- Post Top 60-76mm

### Other Options

- Colour Temperature Option
  - Photocell Option
- [Contact for details](#)

### Optics



Symmetrical

Code	Power	Luminaire Lumens	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included	Driver Type
TAU35F	35.0	2,487	700	Symmetrical	4000	IP66	IK09	5.9	RAL7016 Anthracite Grey	Driver Inc	Fixed
TAU35PEC	35.0	2,487	700		4000	IP66	IK09	6.0	RAL7016 Anthracite Grey	Driver Inc	Fixed
TAU55F	55.0	3,905	1050		4000	IP66	IK09	5.9	RAL7016 Anthracite Grey	Driver Inc	Fixed
TAU55PEC	55.0	3,905	1050		4000	IP66	IK09	6.0	RAL7016 Anthracite Grey	Driver Inc	Fixed



### Dimensions

