

Datasheet

ALFRESCO Urban



Specification Text

The ALFRESCO Urban shall be manufactured from high-pressure die-cast aluminium. It shall have an efficacy of up to 107.0 lm/W and will be capable of producing up to 2,147 luminaire lumens at 4000K with a CRI >80. The wall mounted luminaire provides a diffused aesthetic and comes with photocell, motion sensor and emergency capabilities. It shall have asymmetric optics and is rated at IP65 and IK08.

Specification

Weight: 2.5 kg
Material: Die-cast Aluminium
Paint Finish: RAL7016 Anthracite Grey


Product Description

Simple and classic, ALFRESCO Urban was created to suit many applications. Available with photocell and microwave sensor options, it's the perfect all rounder.

Key Features

- 20.0W
- 1,183 - 2,147 Luminaire Lumens
- Efficacy up to 107.0lm/W
- 2700K, 4000K, CRI>80
- IP65 & IK08
- Lifetime 50,000, L70
- Motion Sensor
- Emergency Compatible
- Colour Temperature

Optics



Asymmetrical 180x90°


IP65	IK08	Colour Temperature	50,000 hrs LIFETIME	5 YEARS WARRANTY	
EM	PEC	2700K	4000K		

Mounting Options

- Wall Mount

Body Type	A	B	C
Standard	340	340	105

All measurements in mm



Code	Power	Luminaire Lumens	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Driver Included	Driver Type
ALFH20F	20.0	2,147	500	Asymmetrical 180x90°	4000	IP65	IK08	2.5	Yes	Fixed
ALFH20FPEC	20.0	2,147	500		4000	IP65	IK08	2.5	Yes	Fixed
ALFH20FEM	20.0	2,147	500		4000	IP65	IK08	2.5	Yes	Fixed
ALFH20FEMPEC	20.0	2,147	500		4000	IP65	IK08	2.5	Yes	Fixed
ALFH20F27K	20.0	1,813	500		2700	IP65	IK08	2.5	Yes	Fixed
ALFH20F27KPEC	20.0	1,813	500		2700	IP65	IK08	2.5	Yes	Fixed
ALFH20F27KEM	20.0	1,813	500		2700	IP65	IK08	2.5	Yes	Fixed
ALFH20F27KEMPEC	20.0	1,813	500		2700	IP65	IK08	2.5	Yes	Fixed