



Kingfisher Lighting

Datasheet

Feeder Pillars

Our feeder pillars are suitable for housing remote control gear and the termination of supply cables. We can supply them pre-wired to make your project hassle-free.



Key Features

- Available in 6 sizes and manufactured from sheet steel which is hot dip galvanised to ISO 1461
- Long-life hinges manufactured from solid stainless steel blocks
- 18mm thick, treated exterior grade plywood backboards (removable for wiring)
- Earth lead connection supplied from the pillar body to the door
- Warning labels fitted in door recess
- Supplied with wedge locks (anti-vandal locks available on request)

Code	External Dimensions (mm)					Backboard		Working Depth	Door Aperture		Weight
	H	W	D	R	O/AH	H	W		H	W	
FPIL15	460	300	150	160	610	290	285	130	280	285	17
FPIL20	700	160	125	300	1000	600	145	105	570	150	14
FPIL30	700	160	150	300	1000	600	145	130	570	150	17
FPIL350	1350	1200	450	400	1750	1170	1180	400	1050	1095	165
FPIL580	1600	2000	450	400	2000	1420	1980	410	1300	2420	405
FPIL590	1600	2500	450	400	2000	1420	2480	410	1300	2420	436
FPIL50	750	250	150	300	1050	650	230	130	550	144	24
FPIL60	850	350	225	300	1150	750	330	205	650	244	26
FPIL70	950	450	250	300	1250	850	430	230	750	344	47
FPIL80	1050	550	275	300	1350	950	530	255	850	444	60
FPIL90	1150	650	300	300	1450	1050	630	280	950	544	75
FPIL100	1250	800	325	325	1550	1150	780	305	1050	695	102
FPIL03	770	700	210	250	1020	685	685	190	600	594	61
FPIL120	1250	1000	325	300	1550	1150	980	305	1050	894	135